

Beamer II Scooter 2005 Specifications

		(Model No. PN2B)	
Engine			
Туре		Two cycle air cooled oil injected	
Displacement		49.3cc	
Bore / Stroke		φ40.0 * 39.2mm	
Compression - Ratio / Pressure		6.8:1 / 90-120psi	
Torque / BHP		5.2N m @ 7000rpm / 1.5BHP	
Estimated MPG		65mpg/75mpg	
Starting		Electrical with Kick starter back up	
Transmission			
Type		Automatic (C.V.T. V-Belt)	
Chassis			
Overall Length		1830mm / 72.0"	
Overall Width		650mm / 25.6"	
Overall High		1100mm / 43.3"	
Wheel Base		1260mm / 49.6"	
Dry Weight		82kg / 180.7lb	
Suspension			
Front		Telescopic Fork	
Rear		Unit Swing Arm / Single Shock	
Brakes			
Front		Hydraulic Disc	
Rear		Mechanical Drum	
Tires			
Front		120/90-10	
Rear		130/90-10	
Tire Pressure	Front	Front 18psi / 1.25kg/cm2 (Cold)	
THE FIESSULE	Rear	Rear 25psi / 1.75kg/cm2 (Cold)	

Beamer II Scooter 2005 Specifications			
		(Model No. PN2B)	
Carburetor			
Make/Size		Mikuni 18mm (Manual Coke)	
Main Jet		85mm	
Pilot Jet		20mm	
Air Mixture Adjustment		Back out ³ / ₄ - 1 ¹ / ₄ turns	
Idle Speed		Idle 1700 - 1900rpm	
Battery			
Jell Acid (Maintenance Free)		12V-4AH/5AH - GTX5L-BS	
·	Main Fuse	7Amp	
Fluids			
Б 1	Type	Unleaded Gasoline 89 octane	
Fuel	Volume	5.5liters / 1.5gal	
2.6.1.011	Type	High grade synthetic 2 cycle injector oil	
2 Cycle Oil	Volume	1.1 liters / 1.2qts	
Transmission	Type	SAE 80/90 weight	
Transmission	Volume	100cc / 3.4oz	
Spark Plug			
NGK (recommended)		BPR7HS	
Nipendenso		W22FRP-U	
Champion		QL82YC	
Electrode Gap		0.6-0.7mm / 0.023"	
GVWR		240kg. / 530lbs.	
GAWR (Front)		76kg. / 167lbs.	
GAWR (Rear)		165kg. / 164lbs.	
Available Colors *Subject to availability		Red	
		Blue	
		Yellow	
		Black	