Viper 70

by E-TON

Just go there!

Viper 70

Cherry Red
Royal Blue
Sunlight Yellow
Black & Yellow

Introducing the 2007 E-TON Viper 70 four-stroke ATV. This Viper includes a 69.3cc four-stroke air-cooled engine, Automatic C.V.T. belt transmission, and a U.S. Forest Service-approved spark arrestor. The 2007 Viper 70 meets or exceeds EPA clean air requirements and is eligible for the California Green Sticker. Includes full six month limited factory warranty. Designed for riders ages 6 and up.

Optional Accessories

- Remote stop switch
- Safety tether switch
- Hi-Flo fuel line kit
- 3” clear stone fuel filter
- Colored handlebar grips
- Tire repair kit
- E-TON safety flag
- Helmets and apparel available on the web site

EON AMERICA.

www.etonamerica.com

Engine			
Type			Four cycle air cooled (EPA Compliant) SOHC
Displacement			69.3cc
Bore / Stroke			φ47.0 * 40mm
Compression Ratio / Pressure			9.0 : 1 /. 110—130psi
Torque / BHP			4.8N ms @ 6500rpm / 6BHP
EPA Approved			Meet or exceeds EPA clean air requirements and CA Green Sticker
Starting			Electrical starter with kick start backup
Transmission			
Type			Automatic (C.V.T. V-Belt)
Chassis			
Overall Length-With-Height			1480mm / 58.3" - 850mm / 33.5" - 860mm / 33.9"
Wheel Base			930mm / 36.1”
Seat Height			670mm / 26.4"
Ground Clearance			100mm / 3.94"
Dry Weight			112kg / 247lbs
Suspension			
Front			Independent A-arms with Adjustable Shocks
Rear			Swing Arm with Adjustable Shock
Brakes			
Front			Dual mechanical drum
Rear			Hydraulic Disc
Tires			
Front			16/8-7
Rear			16/8-7
Tire Pressure	Front	Min	3.2psi / 0.23kg/cm2
		Max	4.0psi / 0.28kg/cm2
	Rear	Min	3.2psi / 0.23kg/cm2
		Max	4.0psi / 0.28kg/cm2
Wheels			
Bolt Pattern		Front	4 x 110mm (P.C.D.)
		Rear	4 x 110mm (P.C.D.)
Carburetor			
Make/Size			SW 18mm (Manual Choke)
Main Jet			0.95mm
Pilot Jet			0.32mm
Air Mixture Adjustment			Back out 1½ - 1¾ turns
Idle Speed			Idle 1700 - 1900rpm
Sprockets			
Front			520x13t
Rear			520x28t
Chain			#520
Battery			
Jell Acid (Maintenance Free)			12V-4AH/5AH - GTX5L
		Main Fuse	7Amp
Fluids			
Fuel	Type		Unleaded Gasoline 89 octane
	Volume		4.5 liters / 1.2 gal
Engine Oil	Type		SAE 20W - 40
	Volume		0.8 liters / 0.84 qt
Transmission	Type		SAE 80W/90
	Volume		120cc / 4.1 oz
Safety Features			
Safety Tether Switch			Optional equipment
Remote Stop Switch			Optional equipment
Enclosed Foot Rest Area			Standard equipment
Enclosed Engine compartment			Standard equipment
Carrying Capacity			
Rack Capacity		Front	N/A
		Rear	N/A
Towing Capacity		Trailer Wgh	N/A
		Tongue Wgh	N/A
Maximum Rider Weight			68.2kg / 190lb
Minimum Rider Age			6 years