



## Lightning 50 ATV Specifications

<b>Lightning 50 (AXL/NXL/TXL-50)</b>	
<b>Engine</b>	
Type	Two cycle air cooled
Displacement	49.3cc
Bore / Stroke	φ40.0 * 39.2mm
Compression	6.8 : 1
Power	5.2hp @ 7000rpm
<b>Transmission</b>	
Type	Automatic (C.V.T. V-Belt)
<b>Chassis</b>	
Overall Length	1330mm / 56.5"
Overall Width	830mm / 32.7"
Overall High	860mm / 33.9"
Wheel Base	950mm / 37.4"
Ground Clearance	102mm / 4"
Dry Weight	85kg / 187.5lb
<b>Suspension</b>	
Front	Dual A-arm / Adjustable Shocks
Rear	Swing Arm / Adjustable Shock
<b>Brakes</b>	
Front	Dual Mechanical drum
Rear	Mechanical drum
<b>Tires</b>	
Front	16*8-7
Rear	16*8-7
Tire Pressure front & rear	7psi Maximum 2psi Minimum (cold)
<b>Wheel</b>	
Bolt Pattern	4 x 110mm
<b>Carburetor</b>	
Make/Size	Mikuni 18mm (Auto Coke)
Main Jet	85mm
Pilot Jet	20mm
Air Mixture Adjustment	Back out ¾ - 1¼ turns Idle 1700 - 1900rpm

## Lightning 50 ATV Specifications

		Lightning 50 (AXL/NXL/TXL-50)
<b>Sprockets</b>		
Front		420x19t
Rear		420x28t
Chain		#420
<b>Battery</b>		
		12V-4AH/5AH - GTX5L-BS
<b>Fluids</b>		
Fuel	Type	Unleaded Gasoline 89 octane
	Volume	4.5liters / 1.2gal
Engine Oil	Type	High grade synthetic 2 cycle injector oil
	Volume	1.0liters / 1gt
Transmission	Type	SAE 80/90 weight
	Volume	100cc / 3.4oz
<b>Spark Plug</b>		
NGK		BPR7HS
Nipendenso		W22FRP-U
Champion		QL82YC
	Electrode Gap	0.6-0.7mm / 0.023"
<b>Maximum Rider Weight</b>		68.2kg / 190lb
<b>Minimum Rider Age</b>		6 years