



Yukon CXL150

by **E-TON**



Just go there!

Yukon CXL 150

Flame Red
Mountain Silver
Royal Blue
Real Tree® Camo

Introducing the 2009 E-TON Yukon II ATV. E-TON's biggest utility ATV, the Yukon II includes a 149.56cc four-stroke air/oil cooled engine, Automatic C.V.T. belt transmission with forward/reverse shifting, front and rear carrying racks, and a U.S. Forest Service-approved spark arrestor. The Yukon II meets or exceeds EPA clean air requirements and is eligible for the California Green Sticker. Includes full six month limited factory warranty. Designed for riders ages 16 and up.

Optional Accessories

- Heavy duty trailer hitch
- Light duty trailer hitch
- E-TON safety flag
- Helmets and apparel available on the web site

ETON AMERICA

www.etonamerica.com

Engine			
Type		Four cycle air/oil cooled (EPA Compliant) SOHC	
Displacement		149.56cc	
Bore / Stroke		ø57.4 * 57.8mm	
Compression Ratio / Pressure		9.7 : 1 / 150-190psi	
Torque / BHP		10.6N m @ 7500rpm / 10.0BHP	
EPA Approved		Meet or exceeds EPA clean air requirements and CA Green Sticker	
Starting		Electrical starter with kick start backup	
Transmission			
Type		Automatic (C.V.T. V-Belt) with forward/reverse shift	
Chassis			
Overall Length-With-Height		1730mm / 68.1" - 980mm / 38.6" - 1070mm / 42.1"	
Wheel Base		1115mm / 43.9"	
Seat Height		700mm / 26.6"	
Ground Clearance		140mm / 5.5"	
Dry Weight		172 kg / 379 lbs	
Suspension			
Front		Independent A-arm Adjustable Shocks @ 3.5" travel	
Rear		Swing Arm Adjustable Shock @ 3.75" travel	
Brakes			
Front		Dual Mechanical Drum	
Rear		Hydraulic Disc	
Tires			
Front		21/7-10	
Rear		22/10-10	
Tire Pressure	Front	Min	3.2psi / 0.23kg/cm2
		Max	4.0psi / 0.28kg/cm2
	Rear	Min	3.2psi / 0.23kg/cm2
		Max	4.0psi / 0.28kg/cm2
Wheels			
Bolt Pattern	Front	4 x 160mm (P.C.D.)	
	Rear	4 x 110mm (P.C.D.)	
Carburetor			
Make/Size		Kei-Hin CVEK-019 26mm with Manual Choke	
Main Jet		1.12mm	
Pilot Jet		0.35mm	
Air Mixture Adjustment		Back out 1 - 2½turns	
Idle Speed		Idle 1600 - 1800rpm	
Sprockets			
Front		520x12t	
Rear		520x24t	
Chain		#520 O-Ring	
Battery			
Jell Acid (Maintenance Free)		12V-9AH - GTX9	
Main Fuse		10Amp	
Fluids			
Fuel	Type	Unleaded Gasoline 89 octane	
	Volume	6.5liters / 1.7gal	
Engine Oil	Type	SAE 30W	
	Volume	1.0liters / 1.0qt	
Transmission	Type	SAE 85/140 weight gear Oil	
	Volume	750cc / 25.4oz	
Safety Features			
Safety Tether Switch		N/A	
Remote Stop Switch		N/A	
Enclosed Foot Rest Area		Standard equipment	
Enclosed Engine compartment		N/A	
Carrying Capacity			
Rack Capacity	Front	14kg / 30 lb	
	Rear	14kg / 30 lb	
Towing Capacity	Trailer Wgh	150kg / 330 lb	
	Tongue Wgh	32kg / 70 lbs	
Maximum Rider Weight		150kg / 330 lbs	
Minimum Rider Age		16 years	



