

2009 Viper 150R



Just go there!

Viper 150R '09

Royal Blue Silver & Black Cherry Red

Introducing the restyled 2009 E-TON Viper 150R ATV. The largest of the Viper series, the Viper 150R maintains the styling of its companion models while providing the power and size a young adult rider desires. The Viper 150R includes a 149.56cc four-stroke air/oil cooled engine, Automatic C.V.T. belt transmission with forward/reverse shifting, and a U.S. Forest Serviceapproved spark arrestor. The Viper 150R meets or exceeds EPA clean air requirements and is eligible for the California Green Sticker. Includes full six month limited factory warranty. Designed for riders ages 16 and up.

Optional Accessories

- Rear carrying rack
- Light duty trailer hitch
- Helmets and apparel available on the web site

ETON AMERICA

www.etonamerica.com

		by E-TON
Engine		
Type		Four cycle air/oil cooled (EPA Compliant) SOHC
Displacement		149.56cc
Bore / Stroke		φ57.4 * 57.8mm
Compression Ratio / Pressure		9.7 : 1 / 150-190psi
Torque / BHP		10.6N m @ 7500rpm / 10.0BHP
EPA Approved Starting		Meet or exceeds EPA clean air requirements and CA Green Sticker Electrical starter with kick start backup
Spark Plug		NGK C7HSA/NGK (Recommended), 0.6-0.7mm gap
Transmission		NOK C/H5A/NOK (Recommended), 0.0-0.7mm gap
Type		Automatic (C.V.T. V-Belt) with forward/reverse shift
Chassis		The state of the s
Overall Length-Width-Height		1665mm / 65.6" - 1010mm / 39.8" - 1070mm / 42.1"
Wheel Base		1090mm / 42.9"
Seat Height		700mm / 26.6"
Ground Cleara	ınce	140mm / 5.5"
Dry Weight		168 kg / 370 lbs
Suspension		
Front		Dual A-arm Adjustable Shocks @ 3.5" travel
Rear		Swing Arm Adjustable Shock @ 3.75" travel
Brakes		
Front		Dual Mechanical Drum
Rear		Hydraulic Disc
Tires		21/7 10
Front		21/7-10
Rear Min		20/11-9 3.2psi / 0.23kg/cm2
1	Front Max	4.0psi / 0.28kg/cm2
Tire Pressure -	Min	3.2psi / 0.23kg/cm2
	Rear Max	4.0psi / 0.28kg/cm2
Wheels	MA	+.upsi/ u.zorg/ciiiz
Bolt Pattern		4 x 110mm (P.C.D.)
Carburetor		() ,
Make/Size		Kei-Hin CVEK-019 26mm with Manual Choke
Main Jet		1.12mm
Pilot Jet		0.35mm
Air Mixture Adjustment		Back out 1 - 21/2turns
Idle Speed		Idle 1600 - 1800rpm
Sprockets		
Front		520x12t
Rear		520x34t
		#520 O-Ring
Battery Jell Acid (Maintenance Free)		12V-9AH - GTX9
Main Fuse		10Amp
Fluids	Main ruse	тулшр
Type		Unleaded Gasoline 89 octane
Fuel -	Volume	9.0 liters / 2.4gal
n	Type	SAE 30W
Engine Oil Transmission	Volume	1.0liters / 1.0qt
	Type	SAE 80/90 weight gear Oil
	Volume	750cc / 25.4oz
Safety Features		
Safety Tether Switch		N/A
Remote Stop Switch		N/A
Enclosed Foot Rest Area		Standard equipment
Enclosed Engin	•	N/A
Carrying Capaci		
Rack Capacity	Front	N/A
	Rear	Optional
	Trailer Wgh	150kg / 330 lb (Optional Kit Available)
Towing Capacity Tongue Wgh		
		32kg / 70 lbs
Maximum Rider Weight		150kg / 330 lbs
Minimum Ride	r Age	16 years