

2009 Viper 70 Silver



Just go there!

Viper 70 Silver

Red Blue Black & Silver

Introducing the restyled 2009 E-TON Viper 70 Silver four-stroke ATV. This Viper includes a 69.3cc four-stroke air-cooled engine, Automatic C.V.T. belt transmission, and a U.S. Forest Service-approved spark arrestor. The 2009 Viper 70 Silver meets or exceeds EPA clean air requirements and is eligible for the California Green Sticker. Includes full six month limited factory warranty. Designed for riders ages 6 and up.

Optional Accessories

- Remote stop switch
- Safety tether switch
- Hi-Flo fuel line kit
- 3" clear stone fuel filter
- Colored handlebar grips
- Tire repair kit
- E-TON safety flag
- Helmets and apparel available on the web site

ETON AMERICA

www.etonamerica.com

Minimum Rider Age

| | | hu 5700 |
|-----------------------------------------|-------------|-----------------------------------------------------------------|
| Engine | | by E-TO n |
| Type | | Four cycle air cooled (EPA Compliant) SOHC |
| Displacement | | 69.3cc |
| Bore / Stroke | | φ47.0 * 40mm |
| Compression Ratio / Pressure | | 9.0 : 1 /. 110—130psi |
| Torque / BHP | | 4.8N ms @ 6500rpm / 6BHP |
| EPA Approved | | Meet or exceeds EPA clean air requirements and CA Green Sticker |
| Starting | | Electrical starter with kick start backup |
| Spark Plug | | NGK CR7HSA/NGK (Recommended), 0.6-0.7 mm Gap |
| Transmission | | |
| Type | | Automatic (C.V.T. V-Belt) |
| Chassis | | |
| Overall Length-Width-Height | | 1510mm / 59.5" - 850mm / 33.5" - 890mm / 31.5" |
| Wheel Base | | 930mm / 36.1" |
| Seat Height Ground Clearance | | 670mm / 26.4" 100mm / 3.94" |
| | | 112kg / 247lbs |
| Dry Weight Suspension | | 112kg / 24/108 |
| Front | | Single A-arm with Adjustable Shocks |
| Rear | | Swing Arm with Adjustable Shock |
| Brakes | | Same and the regulation brook |
| Front | | Dual mechanical drum |
| Rear | | Hydraulic Disc |
| Tires | | |
| Front | | 16/8-7 |
| Rear | | 16/8-7 |
| Fi Tire Pressure | ont Min | 3.2psi / 0.23kg/cm2 |
| | Max | 4.0psi / 0.28kg/cm2 |
| | ear Min | 3.2psi / 0.23kg/cm2 |
| Max | | 4.0psi / 0.28kg/cm2 |
| Wheels | | 4 440 (D.C.D.) |
| Bolt Pattern | Front | 4 x 110mm (P.C.D.) |
| Rear 4 x 110mm (P.C.D.) | | |
| | | SW 22mm (Manual Choke) |
| Main Jet | | 0.95mm |
| Pilot Jet | | 0.32mm |
| Air Mixture Adjustment | | Back out 1½ - 1¾ turns |
| Idle Speed | | Idle 1700 - 1900rpm |
| Sprockets | | |
| Front | | 520x13t |
| Rear | | 520x28t |
| Chain | | #520 |
| Battery | | |
| Jell Acid (Maintenance Free) | | 12V-4AH/5AH - GTX5L |
| Main Fuse | | 7Amp |
| Fluids | | |
| Fuel - | Type | Unleaded Gasoline 89 octane |
| | Volume | 4.5 liters / 1.2 gal |
| Engine Oil — | Type | SAE 20W - 40 |
| | Volume | 0.8 liters / 0.84 qt |
| Transmission — | Type | SAE 80W/90 |
| Volume Safety Features | | 120cc / 4.1 oz |
| | itah | Optional equipment |
| Safety Tether Switch Remote Stop Switch | | Optional equipment |
| Enclosed Foot Rest Area | | Standard equipment |
| Enclosed Engine compartment | | Standard equipment |
| Carrying Capacity | | |
| Rack Capacity N/A | | N/A |
| | | |
| Towing Capacity | Trailer Wgh | N/A |
| | Tongue Wgh | N/A |
| Maximum Rider | | 68.2kg / 190lb |
| Minimum Rider Age | | 6 years |

6 years