



Viper mini 70

by E-TON



Just go there!

Viper mini 70

Cherry Red
Royal Blue
Sunlight Yellow
Black & Yellow

Introducing the 2007 E-TON Viper 70 Mini four-stroke ATV. Small in size, but big in performance, this Viper includes a 69.3cc four-stroke air-cooled engine, Automatic C.V.T. belt transmission, and a U.S. Forest Service-approved spark ar- restor. Also includes a remote stop switch and controller and a safety tether switch. The 2006 Viper 70 Mini meets or exceeds EPA clean air requirements and is eligible for the California Green Sticker. In- cludes full six month limited factory warranty. Designed for riders ages 6 and up.

Optional Accessories

- Hi-Flo fuel line kit
- 3" clear stone fuel filter
- E-TON safety flag
- Tire repair kit
- Helmets and apparel available on the web site

EON AMERICA.

www.etonamerica.com

Engine			
Type	Four cycle air cooled (EPA Compliant) SOHC		
Displacement	69.3cc		
Bore / Stroke	φ47.0 * 40mm		
Compression Ratio / Pressure	9.0 : 1 / 110—130psi		
Torque / BHP	4.8N ms @ 6500rpm / 6BHP		
EPA Approved	Meet or exceeds EPA clean air requirements and CA Green Sticker		
Starting	Electrical starter with kick start backup		
Transmission			
Type	Automatic (C.V.T. V-Belt)		
Chassis			
Overall Length-With-Height	1430mm / 56.3" - 820mm / 32.3" - 800mm / 31.5"		
Wheel Base	930mm / 36.1"		
Seat Height	640mm / 25.1"		
Ground Clearance	80mm / 3.15"		
Dry Weight	110kg / 243lbs		
Suspension			
Front	Independent A-arms with Adjustable Shocks		
Rear	Swing Arm with Adjustable Shock		
Brakes			
Front	N/A		
Rear	Hydraulic Disc		
Tires			
Front	145/70-6		
Rear	145/70-6		
Tire Pressure	Front	Min	3.2psi / 0.23kg/cm2
		Max	4.0psi / 0.28kg/cm2
	Rear	Min	3.2psi / 0.23kg/cm2
		Max	4.0psi / 0.28kg/cm2
Wheels			
Bolt Pattern	Front	Direct attach	
	Rear	Direct attach	
Carburetor			
Make/Size	SW 18mm (Manual Choke)		
Main Jet	0.95mm		
Pilot Jet	0.32mm		
Air Mixture Adjustment	Back out 1½ - 1¼ turns		
Idle Speed	Idle 1700 - 1900rpm		
Sprockets			
Front	520x13t		
Rear	520x28t		
Chain	#520		
Battery			
Jell Acid (Maintenance Free)	12V-4AH/5AH - GTX5L		
Main Fuse	7Amp		
Fluids			
Fuel	Type	Unleaded Gasoline 89 octane	
	Volume	4.5 liters / 1.2 gal	
Engine Oil	Type	SAE 20W - 40	
	Volume	0.8 liters / 0.84 qt	
Transmission	Type	SAE 80W/90	
	Volume	120cc / 4.1 oz	
Safety Features			
Safety Tether Switch	Standard equipment		
Remote Stop Switch	Standard equipment		
Enclosed Foot Rest Area	Standard equipment		
Enclosed Engine compartment	Standard equipment		
Carrying Capacity			
Rack Capacity	Front	N/A	
	Rear	N/A	
Towing Capacity	Trailer Wgh	N/A	
	Tongue Wgh	N/A	
Maximum Rider Weight	68.2kg / 190lb		
Minimum Rider Age	6 years		

