



Yukon CXL150

by E-TON



Just go there!

Yukon CXL 150

Red
Silver
Real Tree® Camo

Introducing the E-TON Yukon II ATV. E-TON's biggest utility ATV, the Yukon II includes a 149.56cc four-stroke air/oil cooled engine, Automatic C.V.T. belt transmission with forward/reverse shifting, front and rear carrying racks, and a U.S. Forest Service-approved spark arrestor. The Yukon II meets or exceeds EPA clean air requirements and is eligible for the California Green Sticker. Includes full six month limited factory warranty. Designed for riders ages 16 and up.

Optional Accessories

- Heavy duty trailer hitch
- Light duty trailer hitch
- E-TON safety flag
- Helmets and apparel available on the web site

ETON AMERICA

www.etonamerica.com

Engine			
Type	Four cycle air/oil cooled (EPA Compliant) SOHC		
Displacement	149.56cc		
Bore / Stroke	ø57.4 * 57.8mm		
Compression Ratio / Pressure	9.7 : 1 / 150-190psi		
Torque / BHP	10.6N m @ 7500rpm / 10.0BHP		
EPA Approved	Meet or exceeds EPA clean air requirements and CA Green Sticker		
Starting	Electrical starter with kick start backup		
Transmission			
Type	Automatic (C.V.T. V-Belt) with forward/reverse shift		
Chassis			
Overall Length-With-Height	1730mm / 68.1" - 980mm / 38.6" - 1070mm / 42.1"		
Wheel Base	1115mm / 43.9"		
Seat Height	700mm / 26.6"		
Ground Clearance	140mm / 5.5"		
Dry Weight	172 kg / 379 lbs		
Suspension			
Front	Independent A-arm Adjustable Shocks @ 3.5" travel		
Rear	Swing Arm Adjustable Shock @ 3.75" travel		
Brakes			
Front	Dual Mechanical Drum		
Rear	Hydraulic Disc		
Tires			
Front	21/7-10		
Rear	22/10-10		
Tire Pressure	Front	Min	3.2psi / 0.23kg/cm2
		Max	4.0psi / 0.28kg/cm2
	Rear	Min	3.2psi / 0.23kg/cm2
		Max	4.0psi / 0.28kg/cm2
Wheels			
Bolt Pattern	Front	4 x 160mm (P.C.D.)	
	Rear	4 x 110mm (P.C.D.)	
Carburetor			
Make/Size	Kei-Hin CVEK-019 26mm with Manual Choke		
Main Jet	1.12mm		
Pilot Jet	0.35mm		
Air Mixture Adjustment	Back out 1 - 2½turns		
Idle Speed	Idle 1600 - 1800rpm		
Sprockets			
Front	520x12t		
Rear	520x24t		
Chain	#520 O-Ring		
Battery			
Jell Acid (Maintenance Free)	12V-9AH - GTX9		
Main Fuse	10Amp		
Fluids			
Fuel	Type	Unleaded Gasoline 89 octane	
	Volume	6.5liters / 1.7gal	
Engine Oil	Type	SAE 30W	
	Volume	1.0liters / 1.0qt	
Transmission	Type	SAE 85/140 weight gear Oil	
	Volume	750cc / 25.4oz	
Safety Features			
Safety Tether Switch	N/A		
Remote Stop Switch	N/A		
Enclosed Foot Rest Area	Standard equipment		
Enclosed Engine compartment	N/A		
Carrying Capacity			
Rack Capacity	Front	14kg / 30 lb	
	Rear	14kg / 30 lb	
Towing Capacity	Trailer Wgh	150kg / 330 lb	
	Tongue Wgh	32kg / 70 lbs	
Maximum Rider Weight	150kg / 330 lbs		
Minimum Rider Age	16 years		

