



Rover GT

by E-TON



Shown with optional equipment

Let the
ROVER GT
take you there!

Mountain Silver
Forest Green

Introducing the 2008 E-TON Rover GT Utility Kart. E-TON's brand-new, versatile, unique sport/utility vehicle includes a powerful four-stroke air cooled engine, automatic C.V.T. belt transmission with forward/reverse shifting, a full body frame with a seat belt, and a U.S. Forest Service approved spark arrestor.

The Rover GT meets or exceeds EPA clean air requirements and is eligible for the California Green Sticker. Includes full six month limited factory warranty. This multi-purpose vehicle was designed for appropriate sized riders of all ages

Optional Accessories

- Portable Cooler
- Helmets and apparel
- Remote Stop Switch
- Front Cargo Rack
- Rear Cargo basket
- 2 styles of Cargo bags

All available through your local dealership and our website.

ETON AMERICA.

www.etonamerica.com

Engine			
Type	Four cycle air cooled (EPA Compliant) SOHC		
Displacement	88.4cc		
Bore / Stroke	φ47.0 * 51.0mm		
Compression Ratio / Pressure	10.2 : 1 / 120-140psi		
Torque / Power	6.1N ms @ 4000rpm / 6.4Ps/8000rpm		
EPA Approved	Meet or exceeds EPA clean air requirements and CA Green Sticker		
Spark Plug	Recommended: NGK CR7HSA/NGK or Nipendenso U22FS-U		
Electrode Gap	0.6-0.7mm or 0.023"		
Starting	Electrical starter		
Transmission			
Type	Automatic (C.V.T. V-Belt) with forward/reverse shift		
Chassis			
Overall Length-Width-Height	2110mm / 83.0" - 1000mm / 39.4" - 1110mm / 43.7"		
Wheel Base	1375mm / 54.1"		
Seat Height	710mm / 28.0"		
Dry Weight	185 kg / 407.9 lbs		
Suspension			
Front	A-arm with dual Adjustable Shocks		
Rear	Swing Arm with Adjustable Shock		
Brakes			
Front	155mm Dual Hydraulic Disc		
Rear	175mm Hydraulic Disc		
Tires			
Front	18/7-10		
Rear	18/8-10		
Tire Pressure	Front	Min	3.2psi / 0.23kg/cm2
		Max	4.0psi / 0.28kg/cm2
	Rear	Min	3.2psi / 0.23kg/cm2
		Max	4.0psi / 0.28kg/cm2
Wheels			
Bolt Pattern	Front	4 x 110mm (P.C.D.)	
	Rear	4 x 110mm (P.C.D.)	
Carburetor			
Make/Size	SVR 22mm with Manual Choke		
Main Jet	0.95mm		
Pilot Jet	0.32mm		
Air Mixture Adjustment	Back out 1½ - 1¾ turns		
Idle Speed	Idle 1700 - 1900rpm		
Sprockets			
Front	520x12t		
Rear	520x32t		
Chain	#520		
Battery			
Jell Acid (Maintenance Free)	12V-5AH - GTX5L		
Fluids			
Fuel	Type	Unleaded Gasoline 92 octane	
	Volume	11 liters / 2.9gal	
Engine Oil	Type	SAE 15W-40	
	Volume	0.9liters / 0.23gal	
Transmission	Type	SAE 80W-90	
	Volume	300cc / 10.2oz	
Safety Features			
Seat Belt	Lap Belt (Standard)		
Remote Stop Switch	Remote Engine Stop Switch (Optional)		
Carrying Capacity			
Maximum Rider Weight	100kg / 200 lbs		
Additional Features			
Rear Cargo Flat Bed (Standard)	Digital dash gauge—Speedometer & Fuel Level (Standard)		
Covered Front Storage Compartment (Standard)	Dash mounted F/R Shift Knob & indicator lights (Standard)		
Trailer Hitch & Accessory Power Outlet (Optional)	Sporty Steering Wheel		
Foot peddle throttle & brakes controls (Standard)	Rear Cargo Basket (Optional)		
Front Cargo Rack (Optional)	Detachable Spot Light (Optional)		
Carpeted floor mat (Optional)			

